



SPECIFICATIONS:

MOTOR: 1/4HP GEAR-DRIVE EP MOTOR, 175RPM.
 SEAL: EXTERNALLY-MOUNTED DRY-RUNNING.
 IMPELLER: ϕ 16" 3-BLADE HYDROFOIL.
 MOUNT: 3" TRICLAMP. OTHER SIZES/TYPES
 AVAILABLE UPON REQUEST.
 MATERIALS: 316SS WETTED PARTS

ϕ 16" 3-BLADE
 HYDROFOIL, 316SS

<p>PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INDCO INCORPORATED. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF INDCO INCORPORATED IS PROHIBITED.</p>			<p>DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL \pm ANGULAR: MACH \pm BEND \pm TWO PLACE DECIMAL \pm THREE PLACE DECIMAL \pm</p>	NAME	DATE	<p>PhG-025E MIXER GENERAL ARRANGEMENT</p>	
				DRAWN	MH		9/20/11
				CHECKED			
				ENG APPR.			
			MATERIAL	MFG APPR.			
			FINISH	Q.A.			
	NEXT ASSY	USED ON		COMMENTS:			
	APPLICATION		DO NOT SCALE DRAWING				
				SCALE: 1:8	WEIGHT:		
				SIZE A DWG. NO. 31Q1029 - PhG-025E	REV. 0	SHEET 1 OF 1	